

Cylinder padlock VERSO® CLIQ V316

With forced locking - without key -

Product description

- Available as mechanical or electromechanical version (V=)
- Housing chrome-plated in brass
- Cylinder, nickel-plated brass satin
- Standard shackle clearance height 25 mm (AUS=LH25)
- Optionally with non-corroding shackles (AUS=LH25-NIRO)
- Other shackle heights (AUS=LH50, LH75, LH28/5)
- Steel shackle, diameter 8 mm, hardened and chrome-plated
- Steel shackle diameter 5 mm at shackle height 28 mm (AUS=LH28/5), hardened and chrome-plated
- With forced locking as standard
- Optionally available without forced locking (AUS2= OHNE ZWANGSSCHL)
- Optionally with hole for fastening a driving guard (VAR=1901043-X-BOHRUNG)
- Standard version as per DIN EN 12320 class 3 (not valid for AUS=LH28/5)
- Standard with dust and rain cover (SUR=1)
- Optionally without dust and rain cover (SUR=0)
- Optionally IP67 certified with protective cap (SUR=2)
- Optionally available for use in potentially-explosive atmospheres in Zone 1 (Ex II 2G) ATEX=II 2G Ex ib IIC T4 Gb

Scope of delivery

- 1 cylinder padlock

Ordering Information

- Subsequent modification to SUR=2 only available if originally ordered as SUR=0
- (VAR=1901043-X-BOHRUNG) Not in conjunction with protective cap SUR=2

Variants that can be ordered

Article number	V=	AUS=	SUR=
V316	M	LH25	1
	E1	LH25	1
	E2	LH25	1
	M	LH50	1
	E1	LH50	1
	E2	LH50	1
	M	LH75	1
	E1	LH75	1
	E2	LH75	1
	M	LH28/5	1
	E1	LH28/5	1
	E2	LH28/5	1
	M	LH25-NIRO	1
	E1	LH25-NIRO	1
	E2	LH25-NIRO	1

