

CH profile knob cylinder eCLIQ

N484,KNF=2



Small tapered knob with 28 mm diameter -without key-

Product description

- Power is supplied exclusively via the key (no battery in the cylinder)
- Available as rotary secured or electronical version (V=)
- Brass cylinder housing components
- Standard finish, satin nickel-plated (OF=MV)
- Standard knob colour satin nickel-plated (KNF=2MV)
- Basic cylinder length 61 mm (C) - A/B (L=30/30) - other installation lengths available - flexible modular system
- Standard locking cam position (SST=30°); differing locking bit position available
- Optionally available with anti drilling protection class 2 (AB=2)
- Cam made of break-proof, corrosion-resistant stainless steel
- Maintenance-free cylinder
- Splash-proof IP54
- Dust and rain cover available (SUR=1) IP55
- Optionally available for use in potentially-explosive atmospheres in Zone 1 (ATEX=II 2G Ex ib IIC T4 Gb)

Scope of delivery

- 1 CH Profile knob cylinder
- 1 cylinder fixing screw M5 x 85 mm

Ordering Information

- The knob is always on the inside of the cylinder (B)

Variants that can be ordered

Article number	KNF=	OF=	L=	V=
N484,KNF=2	2MV	MV/MV	30/30	D
	2MV	MV/MV	30/30	E