

Profile- knob cylinder .534,KNF=2,VAR=FS

With magnetic locking cam reset

Overview of Advantages

- The locking cam is automatically reset to 150° - 210° after actuating the knob
- For use in emergency exit and panic exit devices in accordance with DIN 18252:2018-05 class R1

Product description

- For new systems available in mechanical IKON system SK6 as well as mechatronic systems CLIQ, VERSO®/CLIQ und eCLIQ
- For reorders or extensions available in mechanical IKON systems TK5 / SK5 / TK6 / SK6
- Brass cylinder
- Standard finish, satin nickel-plated (OF=MV)
- Standard knob colour satin nickel-plated (KNF=2MV), additional knob colours and surfaces optionally available
- Number of pin tumblers and basic cylinder length (L=) depends on respective system
- Spherical / Tapered cylinder core head with reinforced key guide
- Cam consisting of break and corrosion-resistant nickel silver profile or sinter metal, depending on system
- Core pins made of special wear-resistant bronze
- Standard with drilling protection (the first set of pins is made of steel and another hardened steel pin is added in the cylinder housing)

Scope of delivery

- 1 profile-knob cylinder with VAR=FS function
- 3 nickel silver keys
- 1 cylinder fixing screw M5 x 85 mm

Ordering Information

- The knob is always on the inside of the cylinder (B)

