

G1.419

Knob with handle grip, anodised aluminium, 30 mm diameter -without key-

Product description

- Available as rotary secured or electronical version (V=)
- Brass cylinder housing components
- Standard finish, satin nickel-plated (OF=MV)
- Standard knob colour nickel silver (KNF=1F2)
- Basic cylinder length 61 mm (C) - A/B (L=30/30) - other installation lengths available - flexible modular system
- Optional, differing basic cylinder length of 56 mm (C) - A/B (L=28/28)
- Standard locking cam position (SST=30°); differing locking bit position available, optionally available with SST=FLEX
- Optionally available with double locking cam (VAR=K901310-X-BIFFAR)
- Optionally available with anti drilling protection class 2 (AB=2)
- Cam made of break-proof, corrosion-resistant stainless steel
- Maintenance-free cylinder
- Splash-proof IP54
- Optionally VdS (SZ=VDS-BZ+, AB=3)
- Optionally DIN EN 15684 with anti drilling protection class 2 (SZ=DIN-D, AB=2)
- Optionally available for use in potentially-explosive atmospheres in Zone 1 (ATEX=II 2G Ex ib IIC T4 Gb)
- Optionally available with classroom function: With this anti-amok function the knob is disengaged as the key is entering the cylinder on the opposite side (VAR=1901509+3+ENTKUPPL.)

Scope of delivery

- 1 profile-knob cylinder
- 1 cylinder fixing screw M5 x 85 mm

Ordering Information

- The knob is always on the inside of the cylinder (B)

