


Profile- knob cylinder VERSO® CLIQ V534,KNF=91



Round knob with handle grip, 25 mm diameter - without key -

Product description

- Available as mechanical or electromechanical version (V=)
- Brass cylinder housing components
- Standard finish, satin nickel-plated (OF=MV)
- Standard knob colour brass, satin nickel-plated (KNF=91MV)
- Basic cylinder length 61 mm (C) - A/B (L=30/30) - other installation lengths available - flexible modular system
- Standard cam position (SST=30°)
- Optionally with magnetic locking cam reset function (VAR=FS)
- Cam made of break and corrosion-resistant nickel silver profile
- Tumbler elements with special wear-resistant alloy
- Dust and rain cover for one side available under (SUR=1)
- Optionally available with anti drilling protection class 2 (AB=2)
- Optionally available for use in potentially-explosive atmospheres in Zone 1 (Ex II 2G) ATEX=II 2G Ex ib IIC T4 Gb
- Optional available without audit trail (V2=OHNE AUDIT)
- Optionally available with classroom function: With this anti-amok function the knob is disengaged as the key is entering the cylinder on the opposite side (VAR=1901509+3+ENTKUPPL.)
- Optionally DIN EN 15684 with anti drilling protection class 2 (SZ=DIN-D, AB=2)

Scope of delivery

- 1 profile-knob cylinder
- 1 cylinder fixing screw M5 x 85 mm

Ordering Information

- The knob is always on the inside of the cylinder (B)

Variants that can be ordered

Article number	KNF=	OF=	L=	V=
V534,KNF=91	91MV	MV/MV	30/30	M
	91MV	MV/MV	30/30	E1
	91MV	MV/MV	30/30	E2