

Push cylinder CLIQ® Go NC40,SERVICE=CLIQGo



Without key

Product description

- Dust and rain cover available (SUR=1) IP55
- Special cylinder for application in closing sleeves optimal for use in glas sliding doors e.g. in conjunction with KESO closing sleeves G.052
- Standard finish, satin nickel-plated (OF=MV)
- 22 mm diameter
- Available with 12, 18 or 22 mm hub (AUS=12, AUS=18, AUS=22)
- Maintenance-free cylinder
- Without guide sleeve as standard (AUS2=OHNE HUELSE)
- Optionally with guide sleeve A (AUS2=A-HUELSE) Key removal in two positions
- Optionally with guide sleeve Z (AUS2=Z-HUELSE) Key removal only in zero position (positive locking)
- Splash-proof IP54
- Dust and rain cover available (SUR=1) IP55

Scope of delivery

- 1 pressure cylinder without guide sleeve as standard
- Optionally 1 pressure cylinder with guide sleeve A or Z and spring guide pin, pressure spring and screw M3x3

Ordering Information

- A rosette is not included in the scope of delivery and can be ordered separately as 1897,T1=1355003

Variants that can be ordered

Article number	AUS=	V=
NC40,SERVICE=CLIQGo	12	E
	18	E
	22	E
	AUS2=OHNE	E
	AUS2=A-HUELSE	E
	AUS2=Z-HUELSE	E

