

Profile- knob cylinder eCLIQ

N534,KNF=2,VAR=FS

With magnetic locking cam reset

Product description

- Power is supplied exclusively via the key (no battery in the cylinder)
- Available as rotary secured or electronic version (V=)
- Brass cylinder housing components
- Standard finish, satin nickel-plated (OF=MV)
- Standard knob colour satin nickel-plated (KNF=2MV)
- Basic cylinder length 61 mm (C) - A/B (L=30/30) - other installation lengths available - flexible modular system
- Optional, differing basic cylinder length of 56 mm (C) - A/B (L=28/28)
- Standard locking cam position (SST=30°); differing locking bit position available, optionally available with SST=FLEX
- Optionally with magnetic locking cam reset function (VAR=FS)
- Optionally available with double locking cam (VAR=K901310-X-BIFFAR)
- Optionally available with anti drilling protection class 2 (AB=2)
- Cam made of break-proof, corrosion-resistant stainless steel
- Maintenance-free cylinder
- Splash-proof IP54
- Dust and rain cover available (SUR=3) IP55
- Optionally VdS (SZ=VDS-BZ+, AB=3)
- Optionally DIN EN 15684 with anti drilling protection class 2 (SZ=DIN-D, AB=2)
- Optionally available for use in potentially-explosive atmospheres in Zone 1 (ATEX=II 2G Ex ib IIC T4 Gb)

Scope of delivery

- 1 profile-knob cylinder
- 1 cylinder fixing screw M5 x 85 mm

Ordering Information

- The knob is always on the inside of the cylinder (B)

