

Vandalism proof wall programming device +CLIQ- Remote CR03

Fixed-site station for programming +CLIQ user keys

Product description

- Permits changes to times and authorisations (depending on key type) as well the read-out of event logs
- Optionally with floating contact for third-party devices (V=FO1) only with V=E3 keys
- Requirement for using V=FO1: key firmware eCLIQ 16.3.3 or VERSO/+CLIQ 16.3.7 or higher
- Acoustic and optical signals for operating status and activity progress
- Connection and data exchange via network cable
- Supports PoE (Power over Ethernet) or external power supply 12-24 V
- Organisation number selectable and visible at the front
- Core exchange module for easy changing of the core by external influence
- Suitable for outdoor usage and vandalism hazard areas
- Splash-proof (SUR=0) IP45
- Optionally available with dust and rain cover (SUR=1) IP65
- Vandalism-resistant IK9
- Electronic-Key adapter Standard (SB=0) for non-IKON SK6 radius profiles
- Optional (SB=3mm) for keys in radius profile PA=45 and PA=46
- Supports the IEEE 802.1X authentication standard
- Permits changes to times and authorisations (depending on key type) as well the read-out of event logs


Scope of delivery

- 1 vandalism proof wall programming device

Variants that can be ordered

Article number

CR03



SUR = 0, SB = 3MM

