

Profile- knob cylinder +CLIQ

.534,KNF=91+CLIQ

Round knob with handle grip, 25 mm diameter - without key -

Product description

- For IKON locking systems in the systems TK5, SK5, SK6, TK6, SK7
- Brass cylinder housing components
- Standard finish, satin nickel-plated (OF=MV)
- Standard knob colour brass, satin nickel-plated (KNF=91MV)
- Basic cylinder length for systems TK5/SK5/SK6 61 mm (C) - A/B (L=30/30), for systems TK6/SK7 71 mm (C) - A/B (L=35/35) - other installation lengths available
- Standard cam position (SST=30°)
- Cam made of break and corrosion-resistant nickel silver profile
- Core pins made of special wear-resistant bronze
- Optionally available for use in potentially-explosive atmospheres in Zone 1 (Ex II 2G) ATEX=II 2G Ex ib IIB T4 Gb
- Optionally available with classroom function: With this anti-amok function the knob is disengaged as the key is entering the cylinder on the opposite side (VAR=1901509+3+ENTKUPPL.)

Scope of delivery

- 1 profile-knob cylinder
- 1 cylinder fixing screw M5 x 85 mm

Ordering Information

- The knob is always on the inside of the cylinder (B)

Variants that can be ordered

Article number	KNF=	OF=	L=	V=	SYS=
.534,KNF=91+CLIQ	91MV	MV	30/30	E1	TK5
	91MV	MV	30/30	E2	TK5
	91MV	MV	30/30	E1	SK5
	91MV	MV	30/30	E2	SK5
	91MV	MV	30/30	E1	SK6
	91MV	MV	30/30	E2	SK6
	91MV	MV	35/35	E1	TK6
	91MV	MV	35/35	E2	TK6
	91MV	MV	35/35	E1	SK7
	91MV	MV	35/35	E2	SK7

