



Product description

- Power is supplied exclusively via the key (no battery in the cylinder)
- Available as rotary secured or electronical version (V=)
- Other side can feature an electronic or rotary-secured design
- Brass cylinder housing components
- Standard finish, satin nickel-plated (OF=MV)
- Basic cylinder length 61 mm (C) - A/B (L=30/30) - other installation lengths available - flexible modular system
- Standard locking cam position (SST=30°); differing locking bit position available
- Optional with anti drilling protection class 2 (AB=2/-, -/2, 2/2)
- Both side locking (GE=BS) and 360° free-wheeling function as standard
- Cam made of break-proof, corrosion-resistant stainless steel
- Maintenance-free cylinder
- Splash-proof IP54
- Optionally available for use in potentially-explosive atmospheres in Zone 1 (ATEX=II 2G Ex ib IIC T4 Gb)
- Dust and rain cover for one or both sides available under (SUR=1/-; -/1; 1/1)

Scope of delivery

- 1 CH Profile double cylinder
- 1 cylinder fixing screw M5 x 85 mm

Variants that can be ordered

Article number	OF=	L=	V=
N481	MV/MV	30/30	D/D
	MV/MV	30/30	E/D
	MV/MV	30/30	D/E
	MV/MV	30/30	aluminium