

# Locking lever cylinder +CLIQ

## .449,AUS=E29+CLIQ



30 mm Diameter, laterally flattened to 22 mm -without key-

### Product description

- For IKON locking systems in the system SK6
- 6 pin tumblers
- Brass cylinder
- Standard finish, matt chrome-plated (OF=MC)
- Other surfaces: satin nickel-plated (OF=MV), brass, mat brushed (OF=MG), polished brass (OF=MP)
- Drilling protection (AB=), additional lateral scanning, security card depending on profile (PR=)
- Spherical cylinder core head with reinforced key guide
- Core pins made of special wear-resistant bronze
- Locking lever path 90°
- Two locking lever end positions
- Fixing with M30x1.5 housing nut
- Key rotation 360° (2 key retraction positions)
- Locking lever SLHB= 1647004 (other locking levers available on request)
- Optionally available for use in potentially-explosive atmospheres in Zone 1 (Ex II 2G) ATEX=II 2G Ex ib IIB T4 Gb

### Scope of delivery

- 1 locking lever cylinder
- 1 housing nut M30 x 1.5 x 4
- 2 core nuts M10 x 0,75 x 3
- locking lever fixed

### Ordering Information

- Not available with drilling protection 2 (AB=2) or 3 (AB=3)
- Please include the desired locking path (SST=) in your order.

### Variants that can be ordered

Article number	OF=	V=	SYS=
.449,AUS=E29+CLI	MC	E1	SK6
Q	MC	E2	SK6

