


Cylinder padlocks CLIQ® Go

N316,SERVICE=CLIQGo

With forced locking - without key -



Product description

- Available as electronical version (V=)
- Housing chrome-plated in brass
- Cylinder, nickel-plated brass satin
- Standard shackle clearance height 25 mm (AUS=LH25)
- Optionally with non-corroding shackles (AUS=LH25-NIRO)
- Other shackle heights (AUS=LH50, LH75, LH28/5)
- Steel shackle, diameter 8 mm, hardened and chrome-plated
- Steel shackle diameter 5 mm at shackle height 28 mm (AUS=LH28/5), hardened and chrome-plated
- With forced locking as standard
- Standard version as per DIN EN 12320 class 3 (not valid for AUS=LH28/5)
- Optionally available without forced locking (AUS2= OHNE ZWANGSSCHL)
- Optionally with hole for fastening a driving guard (VAR=1901043-X-BOHRUNG)
- Standard with dust and rain cover (SUR=3) IP55
- Optionally IP54 without dust and rain cover (SUR=0)
- Optionally IP67 certified with protective cap (SUR=2)
- Maintenance-free cylinder

Scope of delivery

- 1 cylinder padlock

Ordering Information

- Subsequent modification to SUR=2 only available if originally ordered as SUR=0
- (VAR=1901043-X-BOHRUNG) Not in conjunction with protective cap SUR=2

Variants that can be ordered

Article number	V=	AUS=	SUR=
N316,SERVICE=CLIQGo	E	LH25	3
	E	LH50	3
	E	LH75	3
	E	LH28/5	3
	E	LH25-NIRO	3