

Profile double cylinder CLIQ® Go

N531,VAR=1901508,SERVICE=CLIQGo

Especially suited for steel doors/steel security fittings with 17 mm drilling (without profile cutouts) - without keys

Product description


- Available as rotary secured or electronical version (V=)
- Other side can feature an electronic or rotary-secured design
- Brass cylinder housing components
- Front surface shortened (diameter 16.6 ± 0.1 mm). Available on one or both sides (VAR=1901508-5-FRONT/NORM, 1901508-5-NORM/FRONT, 1901508-7-FRONT/FRONT)
- Standard finish, satin nickel-plated (OF=MV)
- Basic cylinder length 61 mm (C) - A/B (L=30/30) - other installation lengths available - flexible modular system
- Optional, differing basic cylinder length of 56 mm (C) - A/B (L=28/28)
- Standard locking cam position (SST=30°); differing locking bit position available, optionally available with SST=FLEX
- Optionally available with double locking cam (VAR=K901310-X-BIFFAR)
- Both side locking (GE=BS) and 360° free-wheeling function as standard
- Cam made of break-proof, corrosion-resistant stainless steel
- Maintenance-free cylinder
- Splash-proof IP54
- Dust and rain protection cap available for one or both sides (SUR=3/-, -/3, 3/3) IP55

Scope of delivery

- 1 profile-double cylinder
- 1 cylinder fixing screw M5 x 85 mm

Variants that can be ordered

Article number	VAR=	V=
N531,VAR=1901508,SERVICE=CLIQGo	1901508-5-FRONT/NO RM	D/D
	1901508-5-NORM/FRONT	D/D
	1901508-7-FRONT/FRONT	D/D
	1901508-5-FRONT/NO RM	E/D
	1901508-5-NORM/FRONT	E/D
	1901508-7-FRONT/FRONT	E/D
	1901508-5-FRONT/NO RM	D/E
	1901508-5-NORM/FRONT	D/E
	1901508-7-FRONT/FRONT	D/E
	1901508-5-FRONT/NO RM	E/E
	1901508-5-NORM/FRONT	E/E
	1901508-7-FRONT/FRONT	E/E



VAR=K901310-X-BIFFAR