



Mortise lock 30900.6

with magnetic trap, DIN direction-independent



Overview of Advantages

- DIN direction-independent latch
- Quiet closing
- Prevents damage to the frame
- Function with fold air of 3-8 mm
- New spring concept with strong compression springs for heavy handles
- Bolt feed: single-turn 12 mm
- Certification according to EN 12209
- Certification according to EN 1634-1 to 3

Product description

- This mortise lock has a magnetic latch and is used in combination with a matching MSL magnetic strike plate B-30900. When the door is open, the latch is flush with the faceplate. When the door is closed, the magnetic latch is only pulled into the frame by the magnetic strike plate when the door has reached its end position. This prevents the latch from hitting the frame or strike plate, ensuring damage-free and quiet closing.

Area of Application

- Room doors and entrance doors in general public buildings such as office buildings, administrative buildings and fire doors.

Note

- Use suitable MSL magnetic strike plate B-30900 (not included in delivery)
- Numeric key included in delivery

Technical data

Forend shape	rounded
Follower	9
Bolt throw	12 mm
Surface	Brush-finished matt
Distance	78mm
DIN direction	DIN direction-independent
Latch material	Plastic (PEEK)
material bolt	Zamak
Material face plate	INOX
Material faceplate	Brush-finished matt
material bolt	Stainless steel
Backset	70
Type of cylinder	RZ
Faceplate dimensions	230x20x3

Article number	11205020
----------------	----------