

# Mortise lock 30900- BL.6

with magnetic trap, DIN direction-independent, visible parts black

## Overview of Advantages

- DIN direction-independent latch
- Elegant appearance thanks to black-coated parts
- Wooden and cylinder screws in black included in delivery
- Quiet closing
- Prevents damage to the frame
- Function with fold air of 3-8 mm
- New spring concept with strong compression springs for heavy handles
- Bolt feed: single-turn 12 mm
- Certification according to EN 12209
- Certification according to EN 1634-1 to 3

## Product description

- This mortise lock has a magnetic latch and is used in combination with a matching MSL magnetic strike plate B-30900. When the door is open, the latch is flush with the faceplate. When the door is closed, the magnetic latch is only pulled into the frame by the magnetic strike plate when the door has reached its end position. This prevents the latch from impacting the frame or strike plate, ensuring damage-free and quiet closing. All visible parts have an elegant black finish and come with a matching strike plate.

## Area of Application

- Room doors and entrance doors in general public buildings such as office buildings, administrative buildings and fire doors.

## Note

- Use matching Black Line MSL magnetic strike plate B-30900 (not included in delivery)
- Scope of delivery: 1 lock, 1 combination key (black), 2 wood screws for mounting (black), 1 cylinder screw (black)

## Technical data

|                                           |                             |
|-------------------------------------------|-----------------------------|
| Forend shape                              | rounded                     |
| Follower                                  | 9                           |
| Distance                                  | 78mm                        |
| DIN direction                             | Independent                 |
| Latch material                            | Plastic (PEEK)              |
| material bolt                             | ZAMAK, KTL coated           |
| Material face plate                       | Stainless steel, KTL coated |
| Panic function                            | ohne Panik                  |
| Material faceplate                        | KTL coated                  |
| material bolt                             | Stainless steel             |
| Dimensions of latch bolt mating component | none                        |
| Backset                                   | 80                          |
| Type of cylinder                          | RZ                          |
| Faceplate dimensions                      | 230x20x3                    |

|                |          |
|----------------|----------|
| Article number | 11205070 |
|----------------|----------|

