

DELTA tubular frame panic mortise lock 19444PE.7

Panic function E, with latch switching

Overview of Advantages

- Trap conversion DINL / DINR
- With latch-bolt function
- No
- Certification according to EN 1125
- Certification according to EN 1634-1 to 3
- Burglary resistant to class RC2 can be achieved in appropriate door systems

Product description

- The door can be opened to exit when locked at any time via the inside handle, a panic bar or a push bar. They pull back the long bolt (panic function). A knob or a handle bar is mounted on the outside. The door can be opened from the outside with the key via the latch-bolt function.

Area of Application

- Security, private service doors, fire doors and escape route doors
- Metal doors (profile doors)

Note

- Suitable for freewheeling cylinders
- On the frame side, only use bolt switch contact MSL 1886.

Technical data

Bolt throw	20 mm
Latch	Reversible
DIN direction	Left / Right reversible
Version	single leaf
Latch material	Inox
material bolt	Inox
Panic function	E
Alternative function	Yes
Material faceplate	Inox
material bolt	Inox
DIN direction	Left / Right reversible
Distance	92 mm
Backset	50
Forend shape	Square
Type of cylinder	PZ - profile cylinder
Faceplate dimensions	270x24x3
Follower	9, one-piece

Article number	10204013
EAN	7630005922859



DELTA tubular frame panic mortise lock 19444PE.7

Panic function E, with latch switching

