

Planet MinE- F/S | 27 dB

8 x 30 mm / 25 x 43 mm | 20 mm | 27 dB

Overview of Advantages

- Drop-down seal for wood and metal doors
- Especially for Minergie, passive and KfW efficient houses
- Increased acoustic insulation with simultaneous air flow
- For closed rooms with ventilation / WC / bathroom (air circulation / air balance)
- Easy planning thanks to slim design, universally applicable for rebated and flush doors
- Drop height up to 20 mm
- Joint acoustic insulation of 27 dB with 7 mm ground air
- Air flow 200 m³/h
- Measured value 30 m³/h at pressure difference of 3.9 Pa (door width 1050 mm)
- High-quality silicone lip, lateral protrusion adjustable
- Easy drop height adjustment
- Slope compensation for 1000 mm door width: 15 mm
- Automatic compensation of sloped floors
- 7-year warranty

Incl. accessories

Planet assembly set MinE-F with 2 mounting brackets (stainless steel), 8 screws and stopping plate, type 1

Tender specification


Automatic door drop-down seal Planet MinE-F / S | 27 dB for rebated acoustic insulation doors with air opening, hinge-side release with automatic compensation for sloping floors, parallel lowering, sealing height up to 20 mm, lip made of high-quality silicone, side mounting, aluminium profiles 8 x 30 mm / 25 x 43 mm, MinE-F channel and bottom sealing equipped with acoustic insulation materials.

Technical data

Groove size	25,3 mm wide and 43.5 mm deep / 8,3 mm wide and 30,5 mm deep
Seal profile	high-quality silicone or high-quality self-extinguishing silicone
Sound absorption value	up to 27 dB at ground air 7 mm
Frame protector plate	stainless steel, for knocking in, 20 x 20 mm
Fastening	on the side with stainless steel mounting bracket and screws
Can be shortened	max. 125 mm
Release	on one side, hinge side
Drop height adjustment	on release pin with 3 mm Allen key
Max. drop height	20 mm
Profile size	8 x 30 mm / 25 x 43 mm
Profile material	Aluminium (both)
Special features	Air flow 30 m³/h at ventilation length 1050 mm and pressure difference of 3.9 Pa

Variants that can be ordered

Order number	Version	Length	can be shortened to	Order placement information
40040F		400 mm		no function
40046F		460 mm	>335 mm	
40059F		585 mm	>460 mm	
40071F		710 mm	>585 mm	
40084F		835 mm	>710 mm	
40096F		960 mm	>835 mm	
40109F		1085 mm	>960 mm	
40121F		1210 mm	>1085 mm	
40134F		1335 mm	>1210 mm	
40146F		1460 mm	>1335 mm	
40200F				per running meter



Features / versions (depending on options)



Floor surfaces



Possible door types (depending on options)

