

EC–CERTIFICATE OF CONFORMITY

0432 –CPD – 0017

In compliance with the Directive 89/106/EEC of the Council of European Communities of 21 December 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to the construction products (Construction Products Directive - CPD), amended by the Directive 93/68/EEC of the Council of European Communities of 22 July 1993, it has been stated that the construction product

Panic exit devices Abloy

Panic exit devices operated by a horizontal bar for single and double leaf doors
as detailed on appendix 2,

placed on the market by

ASSA ABLOY Sicherheitstechnik GmbH
Bildstockstr. 20
72458 Albstadt
Germany

and produced in the factory:

see appendix 1

submitted by the manufacturer to a factory production control and to the further testing of samples taken at the factory in accordance with a prescribed test plan and that the approved body – 0432 *MPA NRW* - has performed the initial type-testing for the relevant characteristics of the product, the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.

This certificate attests that all provisions concerning the attestation of conformity and the performances described in Annex ZA of the standard

DIN EN 1125 : 2008-04
(EN 1125:2008 (D))

were applied and that the product fulfils all the prescribed requirements.

This certificate was first issued on 11. May 2011 remains valid as long as the conditions laid down in the harmonised technical specification in reference or the manufacturing conditions in the factory or the FPC itself are not modified significantly.



Dortmund, 3. November 2011



Dipl.-Ing. H. Jansen
head of the certification body

THIS CERTIFICATE COMPRISES ONE (1) PAGE AND TWO (2) APPENDIXES

THIS DOCUMENT WAS ORIGINALLY WRITTEN IN GERMAN. IN CASE OF DOUBT THE GERMAN VERSION SHALL PREVAIL.

Panic exit devices Abloy

manufacturing plants

product	production plants
locks	<p>Abloy Oy Wahlforssinkatu 20 FIN-80101 Joensuu Finland DO 6.7</p> <p>-----</p> <p>ASSA ABLOY Sicherheitstechnik GmbH Bildstockstr. 20 72458 Albstadt Germany DO 22.0</p>
bars	<p>ASSA ABLOY Sicherheitstechnik GmbH Werk Albstadt Bildstockstr. 20 D-72458 Albstadt Germany DO 30.04</p> <p>-----</p> <p>HEWI Heinrich Wilke GmbH Hagenstrasse 2 D-34454 Bad Arolsen-Mengershausen Germany DO 30.10</p> <p>-----</p> <p>GfS Gesellschaft für Sicherheitstechnik mbH Tempowerkring 15 21079 Hamburg Germany</p>



MATERIALPRÜFUNGSAMT NORDRHEIN-WESTFALEN

Panic exit devices in accordance to EN 1125 for single leaf and double leaf doors

named:

Panic exit devices Abloy

Single leaf door locks

Item no.	VS-type	function	backset	entraxe	forend width	classification											bar no.
						3	7	6	B	1	3	2	W	A	B		
309X ^{b)}	B	Funktion I	30, 35, 45 mm 55 bis 100mm	92 mm PZ 94 mm RZ 72mm PZ 74mm RZ	3 20 mm	3	7	6	B	1	3	2	W	A	B	1, 2, 3	
						3	7	6	0	1	3	2	2	B	B		4
329X ^{b)}	B	Funktion I	30 bis 45 mm 55 bis 100mm	92 mm PZ 94 mm RZ 72mm PZ 74mm RZ	3 20 mm	3	7	6	B	1	3	2	W	A	B	1, 2, 3	
						3	7	6	0	1	3	2	2	B	B		4
409X ^{b)}	B	Funktion I	30, 35, 45 mm 55 bis 100mm	92 mm PZ 94 mm RZ 72mm PZ 74mm RZ	3 20 mm	3	7	6	B	1	3	2	W	A	B	1, 2, 3	
						3	7	6	0	1	3	2	2	B	B		4
509X ^{b)}	B	Funktion I	30, 35, 45 mm 55 bis 100mm	92 mm PZ 94 mm RZ 72mm PZ 74mm RZ	3 20 mm	3	7	6	B	1	3	2	W	A	B	1, 2, 3	
						3	7	6	0	1	3	2	2	B	B		4
529X ^{b)}	B	Funktion I	30 bis 45 mm 55 bis 100mm	92 mm PZ 94 mm RZ 72mm PZ 74mm RZ	3 20 mm	3	7	6	B	1	3	2	W	A	B	1, 2, 3	
						3	7	6	0	1	3	2	2	B	B		4
609 ^{b) c)}	B	Funktion I	30 bis 45 mm 55 bis 100mm	92 mm PZ 94 mm RZ 72mm PZ 74mm RZ	3 20 mm	3	7	6	0	1	3	2	W	A	B	1, 2, 3	
						3	7	6	0	1	3	2	2	B	B		4
629X ^{b) c)}	B	Funktion I	30 bis 45 mm 55 bis 100mm	92 mm PZ 94 mm RZ 72mm PZ 74mm RZ	3 20 mm	3	7	6	0	1	3	2	W	A	B	1, 2, 3	
						3	7	6	0	1	3	2	2	B	B		4
709X ^{b)}	B	Funktion II	30, 35, 45 mm 55 bis 100mm	92 mm PZ 94 mm RZ 72mm PZ 74mm RZ	3 20 mm	3	7	6	B	1	3	2	W	A	B	1, 2, 3	
						3	7	6	0	1	3	2	2	B	B		4
729X ^{b)}	B	Funktion II	30 bis 45 mm 55 bis 100mm	92 mm PZ 94 mm RZ 72mm PZ 74mm RZ	3 20 mm	3	7	6	B	1	3	2	W	A	B	1, 2, 3	
						3	7	6	0	1	3	2	2	B	B		4
309EB ^{b)}	B	Funktion Va	35 bis 80 mm	92 mm PZ 94 mm RZ	3 20 mm	3	7	6	B	1	3	2	W	A	B	1	
319EB ^{b)}	B	Funktion Va	35 bis 80 mm	92 mm PZ 94 mm RZ	3 20 mm	3	7	6	B	1	3	2	W	A	B	1	
319E ^{b)}	B	Funktion I	35 bis 80 mm	92 mm PZ 94 mm RZ	3 20 mm	3	7	6	B	1	3	2	W	A	B	1	
519E ^{b)}	B	Funktion I	35 bis 80 mm	92 mm PZ 94 mm RZ	3 20 mm	3	7	6	B	1	3	2	W	A	B	1	
509E ^{b)}	B	Funktion I	35 bis 80 mm	92 mm PZ 94 mm RZ	3 20 mm	3	7	6	B	1	3	2	W	A	B	1	
809E ^{b)}	B	Funktion II	35 bis 80 mm	92 mm PZ 94 mm RZ	3 20 mm	3	7	6	B	1	3	2	W	A	B	1	
819E ^{b)}	B	Funktion II	35 bis 80 mm	92 mm PZ 94 mm RZ	3 20 mm	3	7	6	B	1	3	2	W	A	B	1	



MATERIALPRÜFUNGSAMT NORDRHEIN-WESTFALEN

All kinds of cylinders do not have influence on the escape function of the lock.

function I: constantly working escape door function. Opening is always possible over the handle.

funktion II: splitted follower, constantly working escape door function from the inside. Opening is always possible over the interior handle from the inside. The external handle will be coupled by an electronically device.

function Va: splitted follower, constantly working escape door function from the inside. Opening is always possible over the interior handle from the inside. The external handle will be coupled or uncoupled by operating the key.

VS-type A: lock for a single or a double leaf door: active or inactive leaf.

VS-type B: lock for a single leaf door.

VS-type C: lock for a double leaf door: only inactive leaf.

bar: indicates the combination between the lock and the panic bar

Horizontal panic bars (bar)

no.	type	coding	classification W
1	Effe 8000	DO 22.0	1
2	HEWI PS 160XA 30°	DO 30.10	2
3	HEWI PS 111XA 30°	DO 30.10	2
4	GfS e-Bar	-	-



alternative and additional equipments

Outside handle

Outside handles in accordance with DIN 18273 with conformity certificate may be used.

Bolt switching contact

Type 031308

Type 031309

Bolt extension

type 819 ZBV

Only in conjunction with locks type 819 E, 519 E, 319 E and 319 EB possible.

Intergrated additional Lock

latch 807.10 with emergency electric strike modell 331/332

Mechatronic striking plate (electric strike)

MEDIATOR modell 65xx. Only in conjunction with locks modell 609 or 629x.

