

No.: DoP-309MB.02

1. Unique identification code of the product-type:

Emergency exit device, for use on escape routes according to EN 179:2008

Lock model 309MB in all variants

2. Intended use/s:

Emergency exit device operated by a lever handle or push pad, for use on escape routes according to EN 179:2008

3. Manufacturer:

ASSA ABLOY
Sicherheitstechnik GmbH
Bildstockstraße 20
72458 Albstadt
GERMANY

4. Authorized representative:

N/A

5. System/s of AVCP:

System 1 according to EN 179:2008

6.a Harmonised standard:

Notified body	Harmonised standard	Certificate of Constancy of performance
MPA NRW, Marsbruchstraße 186; D-44287 Dortmund, identifier:0432	EN 179:2008	0432-CPR-00007-01 (V03)

6.b European Assessment Document:

N/A

7. Declared performance/s:

Declared performance according to EN 179:2008

Essential characteristics	Requirement clauses EN 179:2008	Product performance
Ability to release (for doors on escape routes)	4.1.2 Release function 4.1.3 Release operation 4.1.4 Lever handle design 4.1.5 Push pad design 4.1.6 Double door set 4.1.8 Exposed edges and corners 4.1.11 Push pad installation 4.1.12 Lever handle installation 4.1.13 Operating element projection 4.1.14 Operating element face 4.1.15 Lever handle free end 4.1.16 Lever handle operating gap 4.1.17 Push pad operating gap 4.1.18 Test rod 4.1.19 Push pad release operation 4.1.20 Accessible gap 4.1.21 Door free movement 4.1.22 Top vertical bolt 4.1.24 Keepers 4.1.25 Keepers dimensions 4.1.27 Door mass and dimensions 4.1.28 Outside access device 4.2.2 Release force lever handle Release force push pad 4.2.7 Security requirements	passed, (≤ 1 second) passed passed not applicable not applicable passed, (≥ 0.5 mm) not applicable passed, ($X \geq 120$ mm, $Z \leq 150$ mm) passed, (see classification key (8*)) passed, ($V \geq 18$ mm type A / $V \geq 1400$ mm ² type B) passed, ($U \geq 40$ mm, $W \leq 100$ mm, $\alpha \leq 30^\circ$) passed not applicable passed not applicable passed, (test rod 20 mm) passed not applicable passed not applicable passed; (Weight ≤ 200 kg / width ≤ 1500 mm / height ≤ 2500 mm) passed passed, (≤ 70 N) not applicable passed, (see classification key (7*))
Durability of ability to release against aging and degradation (for doors on escape routes)	4.1.7 Corrosion resistance 4.1.9 Temperature range 4.1.23 Cover for vertical rod 4.1.26 Lubrication 4.2.3 Re-engagement force 4.2.4 Durability 4.2.5 Abuse resistance-Operating element 4.2.6 Abuse resistance-Vertical rod 4.2.8 Final examination Release force lever handle Release force push pad	passed, (see classification key (6*)) passed, (50% threshold) not applicable passed passed, (≤ 50 N) passed, (see classification key (2*)) passed, (500N / 1000N) not applicable passed, (≤ 70 N) not applicable
Self-closing ability C (for fire/smoke doors on escape routes)	4.2.3 Re-engagement force	passed, (≤ 50 N)
Durability of self-closing ability C against aging and degradation (for fire/smoke doors on escape routes)	4.2.4 Durability 4.2.3 Re-engagement force	passed, (see classification key (2*)) passed, (≤ 50 N)
Resistance to fire E (Integrity) and I (Insulation) (for fire doors on escape routes)	4.1.10 Proofed by fire test according EN 1634-1	passed, (see classification key (4*))
Dangerous substances	4.1.29 Note 1 Annex ZA.1	The materials used in this product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations

Classification key according to EN 179:2008

Position	1	2	3	4	5	6	7	8	9	10	
Section	7.1	7.2	7.3	7.4	7.5	7.6	7.7	7.8	7.9	7.10	
Code	3	7	6	B	1	3	5	2	A	B/D	

Pos.	Essential characteristics	Class – Performance	
1	Category of use	3	High frequency of use where there is little incentive to exercise care
2	Durability		Test cycles
		7	200.000
3	Door mass		Door mass [kg]
		6	≤ 200
4	Suitability for use on fire / smoke doors		use
		B	Suitable for use on fire and smoke door assemblies
5	Security (personal protection)	1	All emergency exit devices have a critical safety function, therefore only the top grade is identified for the purposes of this European Standard
6	Corrosion resistance		Corrosion resistance
		3	high corrosion resistance
			test time [h]
			96
7	Security (burglary resistance)		test load [N]
		5	5.000
8	Projection of operating element		Projection of operating element [mm]
		2	≤100
9	Type of operation		Type of operation
		A	Lever handle operation
10	Field of door application		Field of door application
		B	Outward opening single door only
		D	Inward opening single door only

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

N/A

The performance of the product identified above is in conformity with the set of declared performance/s.
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Stefan Fischbach, Managing Director

At Albstadt on 21.09.2020



ASSA ABLOY
Sicherheitstechnik GmbH
Bildstockstraße 20
72458 Albstadt
GERMANY
Tel. +497431 123-0
Fax +497431 123-240
www.assaabloyopeningsolutions.de

ASSA ABLOY is the
global leader in
access solutions.
Every day we help
people feel safe,
secure and
experience a more
open world.

www.assaabloy.com