

Programming key operating notes

For your information:

1. Your key is a high-quality electronic product. Please protect it from dirt and wetness.
2. In the event of a malfunction due to wetness, please just wipe the key dry.
3. The programming key is used for data transmission and does not have a locking function.
4. Battery type:
Your programming key has a standard CR2032 (LiMnO₂) lithium battery.
5. Key ambient temperature:
0 °C to + 70 °C



The EU Declaration of Conformity can be found in the download area of www.assaabloy.de



Disposal:

Packaging materials must be recycled.
The product must be disposed of as electronic scrap.

ASSA ABLOY Sicherheitstechnik GmbH
Attilastr. 61 – 67 • 12105 Berlin • GERMANY

The programming key is your personal identification medium for your locking system.
Please keep it safe!



The key transmits signals as soon as it is inserted in the cylinder!

Comment	Acoustic signal	Optical signal
Normal status	–	–
Battery nearly depleted – Please replace Additional signals will follow	3 x long	3 x long – green
Programming in progress Do not pull out the key	–	1 x short – green per second
Cylinder successfully programmed	1 x long	1 x long – green
No programming is required in this cylinder	2 x short	1 x short – green 1 x short – red
Programming unsuccessful	3 x short	3 x short – red

PB00015000000EN_OC